

New Daylight System DW 200

Production
daylight fixture
flexible and in
small format



Compact
Multipurpose
Weatherproof
Reliable

kobold the world leader for weatherproof daylight systems **expands its IP 54 multipurpose daylight product range with the new 200 Watt lamp head DW 200**. This ultra compact fixture provides all the capabilities of an **Open Face, PAR or soft light** - depending on requirements and selected reflector, lens, softbox or lantern. Conversion is simple: no tools are required.



This fixture, designed for heavy duty use, is the best choice for all lighting applications with the added benefit of maximum reliability even under extreme environmental conditions.

kobold
by bron

The DW 200 System

The multifunctional lamp base is focusable, has an integrated safety devise, ON/OFF switch and a reflector locking system. The L-shape yoke allows 360° rotation.

The lamp base

DW 200

332-0122



Technical data

Dimensions (over all)	130 x 142 x 143 mm / 5.1" x 5.6" x 5.6"
Weight	1.2 kg / 2.7 lbs
Socket	GZY 9.5
Lamp	200 W SE
Cable length	5 m / 16.4 ft
Stand adapter	Ø 16 mm / 5/8"

Open Face reflector


741-0570



Technical data

Dimensions	114 x Ø 140 mm 4.5" x Ø 5.5"
Weight	0,34 kg / 0.75 lb

Textured reflector with adjustable light angle, homogenous, rotationally symmetric illumination, direct use with conversion and diffusion filter.



PAR reflector


741-0571



Technical data

Dimensions	118 x Ø 140 mm 4.7" x Ø 5.5"
Weight	0,35 kg / 0.77 lb

High light output, narrow light angle, for direct use over larger distances or for bouncing via ceilings, walls, canvases, etc., or in combination with PAR lenses for various light characteristics and shapes.



Fresnel lens

741-0544



Technical data

Dimensions	13 x Ø 130 mm 0.5" x Ø 5.1"
Weight	0,21 kg / 0.46 lb

In combination with the PAR reflector and the Fresnel lens, the light becomes a Fresnel light with wide adjustment for directional and soft-focus light.



Bare bulb

744-0298



Technical data

Dimensions	79 x 133 x 137 mm 3.1" x 5.2" x 5.4"
Weight	0,27 kg / 0.6 lb

Using the softbox adapter and a so-called „speed ring“, a softbox or lantern can be mounted. In this application, the entire light of the softbox is collected and the front diffuser is homogeneously illuminated.



Ballasts

AC



EWB 200
742-0150-X

DC



BB200/SL3 with „Slide Lock SL3“ 742-0195



BB200/X with XLR 4 pin plug 742-0191



BB200/C with S12, 2 pin plug 742-0193

kobold
by bron

Bron Elektronik AG
CH-4123 Allschwil / Switzerland
www.bron-kobold.com